

MILITARY SPECIFICATION  
PLASTIC SHEET, ACRYLIC MODIFIED

This amendment forms a part of MIL-P-8184E, dated  
1 February 1989, and is approved for use by all  
Departments and Agencies of the Department of Defense

PAGE 5

Table I, under Max heat deflection temperature, °F: Delete, "236, 240, 244,  
248, 250 and 254" and substitute "234, 237, 241, 244, 246 and 250", respectively

PAGE 7

3.15.3.1, lines 4 and 6: before "square meters)" add "0.1"

PAGE 9

3.15.6, line 2: Delete "4.4.2" and substitute "4.6.12"

PAGE 12

4.4.2.3:

- a. Line 1: After "sample" add "for direct Government purchases"
- b. Line 4, before "Each", Add: "Regardless of the manner employed in selecting sample size,"

PAGE 15

\* Table IX:

- a. Under Requirement paragraph: Delete "3.10" and substitute "3.11"
- b. Under test paragraph:
  - 1. Delete "4.6.6" and substitute "4.6.5"
  - 2. Delete "4.6.12.2" and substitute "4.6.11.2"
- c. Under Characteristic "Stress to craze" add: 3/ See 4.6.12.1 for thicknesses tested."

PAGE 17

4.6.10, line 6: Delete "3.14.4" and substitute "3.15.4"

\* 4.6.12.1:

a. Line 2: After "thickness" insert "0.250 inch".

b. Line 8: After "water" add "maintained"

c. Line 9: After "hours" add new sentence "Throughout all immersion times, the specimens shall not be in contact with one another."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:

Army - ER  
Navy - AS  
Air Force - 11

Preparing Activity:

Navy - AS  
Project No. 9330-1250

Review Activities:

Army - AV, MI, MR  
Navy - EC  
DLA - GS

User Activities:

Army - ME  
Navy - SH, MC